

Digitale manometers

TYPE: ETD-11, klasse 0.4

KASTDIAMETER: 80 MM

Bereiken: -1 - 0 tot 0 - 600 in Bar
0 - 50 tot 0 - 500 in Mbar

Nauwkeurigheid: 0,4%

Aansluiting: 1/4" BSP

Drukeenheid: Bar, KPa, PSI, KG/cm2, MPA

Batterij: 2x 1.5V, AA. Duur > 12 maanden

Display: 4-cijferig LCD display



Specificaties

Auto-zero. Achtergrond licht wit.

Min/Max-geheugen. Grafische lijn weergave van 0 tot 100%.

Behuizing RVS 304. Aansluiting RVS 304.

COMPLEET OVERZICHT TECHNISCHE INFORMATIE ZIE VOLGENDE BLADZIJDE

Bestelcode	Prijs €	Aanwijzing: bar
919001	159,00	-1 - 0
919002	149,00	0 - 1
919003	149,00	0 - 1.6
919004	149,00	0 - 2.5
919005	149,00	0 - 4
919006	149,00	0 - 6
919010	149,00	0 - 10
919016	149,00	0 - 16
919025	149,00	0 - 25
919040	149,00	0 - 40
919060	149,00	0 - 60
919100	149,00	0 - 100
919160	149,00	0 - 160
919250	149,00	0 - 250
919400	149,00	0 - 400
919600	159,00	0 - 600
919201	179,00	0 - 50 Mbar
919202	179,00	0 - 100 Mbar
919203	179,00	0 - 250 Mbar
919204	179,00	0 - 500 Mbar
919000	9,50	beschermkap/IP65

Digitale Manometer - Type ETD-11 / Bladzijde 2

Specificaties	
Overload capacity	<40 bar 150%; > 40 bar 120%
Backlight	Yes
Size	88 mm
Accuracy	0,4% FS, optional 0,2% FS
Working temperature	-10 – 60 °C
Environment temperature	0 ~ 40 °C
Electromagnetic compatibility	EN61326
Measuring rate	3/sec
Measurement medium	Gas/water/oil
Connection standard	C" BSP, on request: M10x1, ¼" NPT, ½" BSP, ½" NPT, M20x1,5
Connection material	304SS (1.4301)
Case	304SS (1.4301)
Batteries	2x Mignon AAA (included)
Battery lifetime	12 months
Weight	0,35 KG

Afmetingen

