

# "ALL-STAINLESS" SOLID-FRONT PRESSURE GAUGES, TYPE PBX-SF-HP




## TYPE PBX-SF-HP, full safety pattern

### STANDARD MODEL

<b>CASE</b>	: bayonet lock, AISI304/1.4301, IP-65 solid front & blow-out back
<b>WETTED PARTS</b>	: spiral wound tube, HP160
<b>WINDOW</b>	: safety glass
<b>DIAL</b>	: aluminium, black figures on white
<b>POINTER</b>	: aluminium, black
<b>CONNECTION</b>	: 9/16" UNF x18 H.P. female (1/4"HP Autoclave) or M16 x 1,5 HP female, AISI316Ti, 1.4571
<b>RANGE</b>	: 0 - 4000 bar upto 0 - 6000 bar, according to DIN 16001 for higher ranges (max. 7000 bar): see below
<b>ACCURACY</b>	: ± 1.0% F.S./class 1



e.g. PBX-SF-HP160XA

TYPE	MODEL	CASE DIAMETER ( Ø in mm)
		160
<b>A</b>		PBX-SF-HP160XA
<b>B</b>		PBX-SF-HP160XB
<b>D</b>		PBX-SF-HP160XD
OPTIONS		EXTRA COSTS
<b>Lx</b>	LIQUID FILLED CASE: ONDINA	PBX-SF-HP160Lx
<b>Range</b>	0 - 7000 bar	