

"SUB SEA" PRESSURE GAUGES, TYPE PBX-SS-CAISSON

TYPE PBX-SS-CAISSON, with pressure tight solid barstock case

STANDARD MODEL

CASE : ø 160 mm - screwed bezel, AISI316/1.4401, pressure tight for decompression tanks

WETTED PARTS : bourdon tube + connection AISI316Ti/1.4571

WINDOW : armoured glass 19 mm

DIAL : aluminium, black figures on white

POINTER : aluminium, black

CONNECTION : 1/2 " BSP or 1/2 " NPT

RANGE : 0-10 upto 0-600 Meter sea water, acc. to EN 837-1 for higher ranges see page 55 (max. 1600 bar)

ACCURACY : ± 1.0% F.S. / class 1

MOVEMENT : AISI304/1.4301

APPLICATION : for use inside decompression chambers with vent connection for ambient pressure with air filter for the "room" pressure

OPTIONS : see page 57-58



TYPE	MODEL CAISSON Dimensions	UNIT PRICE
<p align="center">B</p> <p>PBX-SS-CAISSON-XB</p>		

OPTIONS	EXTRA COSTS	
class 0.6% F.S.	±0.5 / 0.6 %F.S. (class 0.5 or 0.6)	
class 0.25% F.S.	±0.3 or 0.25 %F.S. (class 0.3 or 0.25); Bourdon tube of Copper-beryllium	
Mirrorscale	for accurate reading of the gauge	
Calibration certificate	Certificate traceable to international standards (NET PRICE)	