

"SUB SEA" PRESSURE GAUGES, TYPE PBX-SS-ED

TYPE PBX-SS-ED, with pressure tight solid barstock case: max 4000 metres

STANDARD MODEL

CASE : \varnothing 100 mm - screwed bezel, AISI316/1.4401, pressure tight for depths down to 4000 metres

WETTED PARTS : bourdon tube + connection AISI316Ti/1.4571

WINDOW : armoured glass 35 mm

DIAL : aluminium, black figures on white

POINTER : aluminium, black

CONNECTION : 1/2 " BSP or 1/2 " NPT

RANGE : 0-6 upto 0-60 bar, acc. to EN 837-1
for higher ranges see page 55 (max. 1600 bar)

ACCURACY : \pm 1.0% F.S. / class 1

MOVEMENT : AISI304/1.4301

APPLICATION : for operating at great depths of sea water and in hyperbaric conditions

OPTIONS : see page 55-56



TYPE	MODEL ED "EXTRA DEEP"	DIMENSIONS	UNIT PRICE																						
A		<table border="1"> <tr><th colspan="2">PBX-SS-ED100XA</th></tr> <tr><th>DIM</th><th>CASE</th></tr> <tr><td></td><td>\varnothing 100 MM</td></tr> <tr><td>A</td><td>124</td></tr> <tr><td>B</td><td>91</td></tr> <tr><td>C</td><td>22</td></tr> <tr><td>E</td><td>109</td></tr> <tr><td>T</td><td>20</td></tr> <tr><td>HEX</td><td>22</td></tr> </table>	PBX-SS-ED100XA		DIM	CASE		\varnothing 100 MM	A	124	B	91	C	22	E	109	T	20	HEX	22					
		PBX-SS-ED100XA																							
DIM	CASE																								
	\varnothing 100 MM																								
A	124																								
B	91																								
C	22																								
E	109																								
T	20																								
HEX	22																								
C		<table border="1"> <tr><th colspan="2">PBX-SS-ED100XC</th></tr> <tr><td>A</td><td>124</td></tr> <tr><td>B</td><td>91</td></tr> <tr><td>C</td><td>30</td></tr> <tr><td>E</td><td>132</td></tr> <tr><td>T</td><td>20</td></tr> <tr><td>HEX</td><td>22</td></tr> </table>	PBX-SS-ED100XC		A	124	B	91	C	30	E	132	T	20	HEX	22									
		PBX-SS-ED100XC																							
A	124																								
B	91																								
C	30																								
E	132																								
T	20																								
HEX	22																								
D		<table border="1"> <tr><th colspan="2">PBX-SS-ED100XD</th></tr> <tr><td>A</td><td>124</td></tr> <tr><td>B</td><td>91</td></tr> <tr><td>C</td><td>22</td></tr> <tr><td>D</td><td>175</td></tr> <tr><td>E</td><td>132</td></tr> <tr><td>H</td><td>7</td></tr> <tr><td>F</td><td>8</td></tr> <tr><td>P</td><td>150</td></tr> <tr><td>T</td><td>20</td></tr> <tr><td>HEX</td><td>21</td></tr> </table>	PBX-SS-ED100XD		A	124	B	91	C	22	D	175	E	132	H	7	F	8	P	150	T	20	HEX	21	
		PBX-SS-ED100XD																							
A	124																								
B	91																								
C	22																								
D	175																								
E	132																								
H	7																								
F	8																								
P	150																								
T	20																								
HEX	21																								
J		<table border="1"> <tr><th colspan="2">PBX-SS-ED100XJ</th></tr> <tr><td>A</td><td>124</td></tr> <tr><td>B</td><td>91</td></tr> <tr><td>C</td><td>30</td></tr> <tr><td>D</td><td>175</td></tr> <tr><td>E</td><td>132</td></tr> <tr><td>F</td><td>8</td></tr> <tr><td>H</td><td>7</td></tr> <tr><td>P</td><td>150</td></tr> <tr><td>T</td><td>20</td></tr> <tr><td>HEX</td><td>21</td></tr> </table>	PBX-SS-ED100XJ		A	124	B	91	C	30	D	175	E	132	F	8	H	7	P	150	T	20	HEX	21	
		PBX-SS-ED100XJ																							
A	124																								
B	91																								
C	30																								
D	175																								
E	132																								
F	8																								
H	7																								
P	150																								
T	20																								
HEX	21																								
LX	GLYCERINE FILLED CASE		16,50																						
	SILICONE OIL FILLED CASE		36,50																						